

SRW-5500 / SRW-5000 信号変換機能

記録フォーマット			HD-SDI出力	SD-SDI出力	Format Convert出力*1 (信号フォーマットをメニューにて選択)	
テープフォーマット	走査線 / 映像サンプリング方式	フレーム / フィールド周波数				
HDCAM-SR*2	1080/4:4:4*2	23.98PsF*2	1080/4:4:4/23.98PsF	*4 525/59.94i*1	1080/4:2:2/23.98PsF 1080/4:2:2/59.94i 720/4:2:2/59.94P	
		24PsF*2	1080/4:4:4/24PsF	*4	1080/4:2:2/24PsF 1080/4:2:2/60i	
		25PsF*2	1080/4:4:4/25PsF	625/50i*1	1080/4:2:2/25PsF	
		29.97PsF*2	1080/4:4:4/29.97PsF	525/59.94i*1	1080/4:2:2/29.97PsF	
		30PsF*2	1080/4:4:4/30PsF	*4	1080/4:2:2/30PsF	
		50i*2	1080/4:4:4/50i	625/50i*1	1080/4:2:2/50i 720/4:2:2/59.94P	
		59.94i*2	1080/4:4:4/59.94i	525/59.94i*1	1080/4:2:2/59.94i	
		60i*2	1080/4:4:4/60i	*4	1080/4:2:2/60i	
HDCAM-SR または HDCAM	1080/4:2:2	23.98PsF	1080/4:2:2/23.98PsF	*4 525/59.94i*1	1080/4:4:4/23.98PsF 1080/4:2:2/59.94i 720/4:2:2/59.94P	
		24PsF	1080/4:2:2/24PsF	*4	1080/4:4:4/24PsF 1080/4:2:2/60i	
		25PsF	1080/4:2:2/25PsF	625/50i	1080/4:4:4/25PsF	
		29.97PsF	1080/4:2:2/29.97PsF	525/59.94i	720/4:2:2/59.94P 1080/4:4:4/29.97PsF	
		30PsF	1080/4:2:2/30PsF	*4	1080/4:4:4/30PsF	
		50i	1080/4:2:2/50i	625/50i	1080/4:4:4/50i 720/4:2:2/59.94P	
		59.94i	1080/4:2:2/59.94i	525/59.94i	1080/4:4:4/59.94i	
	60i	1080/4:2:2/60i	*4	1080/4:4:4/60i		
	1035/4:2:2	59.94i	1035:4:2:2/59.94i	525/59.94i	*4	
		60i	1035/4:2:2/60i	*4	*4	
	HDCAM-SR	720/4:2:2	59.94P	720/4:2:2/59.94P	525/59.94i	1080/4:2:2/59.94i
	Digital Betacam*3	525/4:2:2*3	59.94i	1080/4:2:2/59.94i	525/59.94i*3	720/4:2:2/59.94P
625/4:2:2*3		50i	1080/4:2:2/50i	625/50i*3	720/4:2:2/50P	

*1 別売のHKSR-5001が必要です。
 *2 別売のHKSR-5003が必要です。
 *3 別売のHKSR-5002が必要です。
 *4 信号は出力されません。